## REMARKS

Claims 1-28 are pending. Claims 1-6 and 9-28 are rejected under 35 U.S.C. § 102(a). Claims 7-8 are objected to. Claims 1 and 24 are amended.

The specification has been a mended to correct a numerical error in applicant's admitted prior art. Referring to Figure 1, sub-window 20, having a 66.7 µsec duration, discloses 256 chips and 512 sample positions. Thus, time slot 10, having a 667 µsec duration (page 5, lines 8-9), has 2560 chips and 5120 sample positions. No new matter is added.

Examiner requires a drawing correction to label Figure 1 Prior Art. The proposed drawing amendment is attached. This correction is also being separately mailed on formal drawings.

Independent claims 1 and 24 are rejected as being anticipated by applicant's admitted prior art. Examiner correctly notes that applicant's admitted prior art discloses a time slot window 10 and a search window 20. The search window 20 is typically on the order of one-tenth the duration of the time slot 10. Claim 1, as amended, recites "A wireless receiver, comprising: at least one antenna for receiving a plurality of frames in a form of a plurality of paths; wherein each of the plurality of frames comprises a plurality of time slots; wherein each of the plurality of time slots comprises a plurality of symbols; wherein each of the plurality of paths has a corresponding sample position; and wherein the plurality of symbols comprise a primary synchronization code symbol; circuitry for correlating a primary synchronization code across a group of the plurality of symbols; circuitry for identifying a plurality of path positions within the group, wherein each of the plurality of path positions corresponds to a respective one of a plurality of largest-amplitude paths represented within the group as detected in response to the circuitry for correlating; circuitry for defining a plurality of sub-windows within one of the plurality of time slots." (emphasis added). Claim 24, as amended, recites "A method of operating a wireless receiver, comprising the steps of: receiving a plurality of frames in a form of a plurality of paths along at least one antenna; wherein each of the plurality of frames comprises a plurality of time slots; wherein each of the plurality of time slots

719783099

comprises a plurality of symbols; wherein each of the plurality of paths has a corresponding sample position; and wherein the plurality of symbols comprise a primary synchronization code symbol; correlating a primary synchronization code across a group of the plurality of symbols; identifying a plurality of path positions within the group, wherein each of the plurality of path positions corresponds to a respective one of a plurality of largest-amplitude paths represented within the group as detected in response to the circuitry for correlating; defining a plurality of sub-windows within one of the plurality of time slots." (emphasis added).

The invention of claims 1-28, defines a plurality of sub-windows 921-924 within a single time slot as shown in Figure 6. These sub-windows are defined by circuit 56 (Figure 4) as described at step 56<sub>ml</sub> (Figure 5) at page 16, lines 14-15. These sub-windows in a single time slot are not disclosed in applicant's admitted prior art. Moreover, the present invention is advantageously compared to the prior art at page 19, lines 1-24. Therein, a preferred embodiment of the present invention details a 97% reduction in computational complexity. Thus, applicant respectfully submits that claims 1-28, as amended, are patentable in view of admitted prior art.

In view of the foregoing, applicant respectfully requests reconsideration and allowance of claims 1-28. If the Examiner finds any issue that is unresolved, please call applicant's attorney by dialing the telephone number printed below.

Respectfully submitted,

Robert N. Rountree Attorney for Applicant

Reg. No. 39,347

Robert N. Rountree, LLC 70360 Highway 69 Cotopaxi, CO 81223 Phone/Fax: (719) 783-0990